LABDEX

Circulating Water Bath LX50CWB

Email: info@labdex.com **website:** www.labdex.com

Description

Circulating Water Bath LX50CWB is a benchtop thermostatic circulating bath with an inner and external circulation system, a temperature range from RT +5 to 100˚C with ±0.1˚C precision. Designed with PID microprocessor temperature control, audible and visible tracking alarm system for temperature and water level ensures precise and reliable operation.

Specifications

Capacity	6.7 L
Temperature range	RT+5-100℃
Precision	±0.1
Pump flow rate	8L/min
Power	1050 W
Voltage supply	220V 50Hz
Interior dimensions	150 x 160 x 150 mm
External dimensions	200 x 335 x 400 mm
Net weight	6 Kg
Packing dimensions	470 x 300 x 560 mm
Gross weight	8 Kg

Features

- LCD display
- Equipped with PID microprocessor temperature controller
- Audible and visual alarm for temperature and water level
- Built-in powerful pressure suction pump
- It has an optional RS485 port for connecting a computer to record the parameters and the variation of the temperature (Option)

Applications

- Used in scientific research, medical, and industry to provide precise and constant temperature and auxiliary heating.

71-75 Shelton Street Covent Garden, London WC2H 9JQ UK.
Email: info@labdex.com | Website: www.labdex.com